

### 3. Extreme Environment

## Molded Vapor Tight Luminaire


# VPVT

#### DIMENSIONS




**NOW AVAILABLE IN LED!**

**NARROW 1 LIGHT**



**STANDARD UNIT**



Dimensions are subject to change. For critical applications, verify all dimensions with factory.



Available in 2', 4', and 8' lengths, 1, 2 & 3 lamp T8, T5, T5HO and LED configurations. Weather resistant housing ideal for parking garages, food processing areas, refrigerated storage, marinas, or any area where moisture protection is required. Internal gear tray replaces traditional strip fixture insert, reducing both weight and expense. Poured in place gasket and latches seal the enclosures from most hostile environments. Polycarbonate or stainless steel and tamperproof latches available. Optional stainless steel snap-in mounting brackets reduce installation time and eliminate mounting holes in fixture body. For individual or continuous row with optional watertight hubs. Optional specular aluminum wide distribution reflector available.

#### HOUSING

Heavy-duty unsaturated fiberglass reinforced polyester housing with poured in place gasketing. Flame class V-0, 5VA.

#### ELECTRICAL

Energy saving electronic ballasts comply with Federal Energy Efficiency standards. Ballasts are <10% THD and include 5 year manufacturer's warranty. Ballasts operate on 120V-277V (UNV) unless specified otherwise. LED: Highest quality driver, emitters and power supply for long life. Different color temperature available.

#### SHIELDING

Ribbed diffuser is molded of UV stabilized acrylic/DR blend to resist breakage and maintain flexibility. Optional polycarbonate lens available in 2' and 4' only. Water clear lens is also available. Single lamp narrow unit is standard with a polycarbonate lens. Also available diffuse lens.

#### CERTIFICATION

All units bear UL wet location label. IP67 Certified. National Sanitation Foundation (NSF) approved components. Manufactured in the USA. ARRA and BAA compliant. Passed 1500 PSI high pressure hose down test. CEE Verified. Ballasts, and Fixture operates up to 70 C Temperature.

#### ORDERING

MODEL	LAMP	WATTAGE	VOLTAGE
VPVT	2	17T8 14T5	120V 277V
2' unit		24T5HO LED8W 55W Flat Panel Board Array	UNV
4' unit	1 2 3	32T8 28T5 54T5HO LED18W 55W Flat Panel Board Array	
8' unit	1 2 2 4 6 55W	96T8 96T8HO 54T5HO 32T8-8TD 28T5-8TD 18W LED-8TD 23W LED-8TD Flat Panel Board Array	

#### OPTIONS:

- EM – Emergency
- SSL – Stainless Steel Latches
- HUB – Wet Location Hub
- TP – Tamperproof Hardware
- SSMB – Stainless Steel Mounting Brackets
- SA95 – Specular Aluminum Reflector (Minimum 91% Reflectance)
- OC – Factory Installed High Bay Occupancy Sensors
- SPM HUB – Single Point Mount Hub
- POLY – Polycarbonate Diffuser
- CP – Factory Installed Cord and Plug (Specify Voltage & Length)
- WCL – Water Clear Lens
- FAL – Frosted Acrylic Lens
- LNST – Lens Tether
- WDR – Wide Distribution Reflector (Specular Aluminum)
- CMB – 90 degree corner mounting bracket
- N – Narrow Housing
- PMB – Pivot Mounting Bracket



JOB NAME:

FIXTURE TYPE:

MODEL NO: