



DIMENSIONS

Dimensions are subject to change. For critical applications, verify all dimensions with factory.



ORDERING

Provides direct/indirect, soft, uniform illumination combined with a shielded direct light source. Curved perforated details combine recessed fixture advantages with efficient indirect lighting. Perforated basket with center parabolic cross baffle backed with reflective white acrylic control glare and veiling reflections. Shielding is easily removed for re-lamping. Flanged fixture available for plaster ceilings.

HOUSING

Die formed heavy gauge steel housing unitized into one piece. Also available as a retrofit kit for deep parabolic housing.

ELECTRICAL

Energy saving electronic ballasts comply with Federal Energy Efficiency standards. Ballasts are <10% THD and include 5 year manufacturer's warranty. Ballasts operate on 120V-277V (UNV) unless specified otherwise.

SHIELDING

Perforated diffuser element with matte white acrylic overlay and center parabolic cross baffle.

FINISH

All metal parts pretreated with a phosphate bonding process and post-painted with an electrostatically applied high temperature baked matte white enamel for superior quality and durability.

CERTIFICATION

All units bear UL label. Made in U.S.A. Suitable for damp location. ARRA and BAA compliant.

| <u>MODEL</u> | <u>LAMP QTY</u> | <u>WATTAGE/TYPE</u> | <u>VOLTAGE</u> |
|---------------|-----------------|---------------------|----------------|
| RDI-22 | 2 | 17T8 | 120 |
| 2x2 unit | 3 | 14T5 24T5HO | 277 UNV |
| RDI-24 | 2 | 32T8 | |
| 2x4 unit | 3 | 28T5 54T5/HO | |

OPTIONS:

- EM** - Emergency
- DM** - Dimming
- Prefix M** – Flanged Unit
- Prefix S** – Surface Unit
- 20G** – 20 Gauge Housing

| |
|---------------|
| JOB NAME: |
| FIXTURE TYPE: |
| MODEL NO: |

