



8. Recessed

LED Recessed Module

K85LED

DIMENSIONS



Dimensions are subject to change. For critical applications, verify all dimensions with factory.



Recessed LED module available in 1x4, 2x2, AND 2x4. Flush steel hinged and latched doorframe, screw assembled for simple diffuser replacement. Integral metal to metal light seal channels eliminate light leakage on all four sides. Fixture housing flanges rolled to eliminate sharp edges.

HOUSING

Die formed heavy gauge steel housing welded for rigidity and structural stability.

LED

CRI>83

PF>90

Up to 50% Energy Savings

Solid state driver

5 year warranty

SHIELDING

100% virgin acrylic prismatic is standard. Consult option sheet for other shieldings.

FINISH

All metal parts are phosphate coated and painted after fabrication with baked white enamel electrostatically applied providing a durable finish with a minimum 89% reflectance.

CERTIFICATION

All units bear UL label. Made in U.S.A. ARRA and BAA compliant. 5 YEAR WARRANTY.

ORDERING

<u>MODEL</u>	<u>SIZE</u>	<u>WATTAGE TYPE</u>	<u>VOLTAGE</u>
K85LED			120 277 UNV
	1x4 unit	2 Board Strip 40 W 3500 LUMENS	
	2x2 unit	2 Board Strip 40 W 4,000 LUMENS	
	2x4 unit	4 Board Strip 70 W 6500 LUMENS	

OPTIONS:

EM - Emergency

DM - Dimming (Specify Type)

WH92 - High Reflective White

OPAL - Opal Lens

125A12 - .125" Thick Pattern 12 Lens

DL - Damp Location

JOB NAME:

FIXTURE TYPE:

MODEL NO:

