



**DIMENSIONS**



Dimensions are subject to change. For critical applications, verify all dimensions with factory.



**ORDERING**

Opal diffuser envelops fixture housing in a smooth architectural line with accent on simplicity of design. Two different sizes (14" and 19") Designed for ceiling or wall surface mounting. Optional tamperproof hardware. A 12W LED is comparable to 50W HID. A 24W LED is comparable to 150-175W HID.

**HOUSING**

Die formed heavy gauge steel housing.

**ELECTRICAL**

High efficiency electronic constant current Class II 120/277V driver.

**LED COLOR**

Standard in 5000K. Consult factory for other Kelvin temperatures.

**SHIELDINGS**

Soft white acrylic diffuser is standard. Optional white polycarbonate, fluted acrylic, and mushroom acrylic.

**FINISH**

Housing is finished inside and out with premium grade baked white enamel with a minimum reflectance of 89%. Optional black paint for exterior of housing.

**CERTIFICATION**

Suitable for wet location. Made in USA. ARRA compliant. UL listed. 3 year warranty.

<u>MODEL</u>	<u>WATTAGE</u>	<u>VOLTAGE</u>
<b>JOLED14</b> 14" diameter	12W	UNV (120/277)
<b>JOLED19</b> 19" diameter	24W	

**OPTIONS**

- EM** – Emergency
- LEX** – Polycarbonate Diffuser
- FLA** – Fluted Acrylic
- MOA** – Mushroom Acrylic
- TP** – Tamperproof Hardware
- CC** – Custom Color (specify color)



JOB NAME:
FIXTURE TYPE:
MODEL NO: