



DIMENSIONS



DLC APPROVED

The CHRLED series is designed for recessed applications such as offices, schools and other institutions. It offers the look and feel of a fluorescent luminaire. High reflectance optical engine delivers main beam focus through optically designed acrylic lens. Linear arrayed LED modules provide soft, effective lumination with no hot spots.

HOUSING

Die formed heavy gauged cold rolled steel. For use with standard 15/16" grid T-bar ceilings with earthquake feature.

LED COLOR

Standard in 4000K. Consult factory for other Kelvin temperatures.

ELECTRICAL

350ma driver suitable for 120v-277v operation. Available in 2 wattages to equal or exceed the output of conventional fluorescent lamps. Driver contains control lead for daylight savings or occupancy control. LM80 certified low wattage LEDs.

SHIELDING

The Lumieo® acrylic diffuser center "V" adds character to the optical assembly.

FINISH

Matte white, high reflectivity powder coat finish.

CERTIFICATION


All units bear UL label. ARRA & BAA Compliant 5 year warranty. Design Lights Consortium Certified.

Dimensions are subject to change. For critical applications, verify all dimensions with factory.

ORDERING



| <u>MODEL</u> | <u>WATTAGE</u> | <u>VOLTAGE</u> |
|--------------------|----------------|----------------|
| CHRLED 2x2 unit | 45W | UNV (120/277) |



OPTIONS:

- DM – Dimming
- CA – Clear Acrylic Diffuser

| |
|-----------|
| JOB NAME: |
| |
| MODEL NO: |

