


DIMENSIONS



Dimensions are subject to change. For critical applications, verify all dimensions with factory.



ORDERING

Available in nominal lengths up to 8'-0" sections, T5 or T8 operation, custom lengths available upon request. For continuous runs please consult factory with specific wiring instructions. Simple clean linear lines allow for this fixture to blend aesthetically into almost any space. Mounting can be accomplished using adjustable aircraft cables or rigid stems. Wall mount is also available.

HOUSING

Die formed welded 20 gauge cold rolled steel. Uplight fixtures are provided with 1 row of 1/2" apertures along top of the housing which provide approximately 12% uplight.

ELECTRICAL

Energy saving electronic ballasts comply with Federal Energy Efficiency standards. Ballasts are <10% THD and include 5 year manufacturer's warranty. Ballasts operate on 120V-277V (UNV) unless specified otherwise.

DIFFUSERS

Pattern A12 acrylic lens is standard. Optional opal lens or cross blade.

FINISH

All parts finished with white polyester powder coat with minimum 89% reflectivity. Standard color is white. Other colors are available upon request.

CERTIFICATION

All units bear UL label. Made in U.S.A. Suitable for damp location. ARRA and BAA compliant.

<u>MODEL</u>	<u>LAMP QTY</u>	<u>LENGTH</u>	<u>TYPE</u>	<u>MOUNTING</u>	<u>VOLTAGE</u>
S44	1	48"	T8	AC – Aircraft Cable (48" Standard) ST – Stem (24" Standard) WM – Wall Mount S – Surface (Direct Only)	120
	2		T5		277
	4	96" XX – Custom Length	T5HO		UNV

OPTIONS:

- EM - Emergency
- DM - Dimming
- CC - Custom Color
- OAL – Opal Acrylic Lens
- WCB – White Cross Baffle



JOB NAME:
FIXTURE TYPE:
MODEL NO: