




DIMENSIONS



*Depth for HPS fixtures is 3-3/4"

Dimensions are subject to change. For critical applications, verify all dimensions with factory.



ORDERING

Available for energy efficient PL 1 and 2 lamp and low wattage HPS sources. Ideal for hotels, motels, walkways, entrances, garages, vanities, stairways, and any area where low wattage, high illumination is desired. Gasketed for dust and moisture resistance. Optional photocell for dusk to dawn operation. Ideal for wet locations.

HOUSING

One piece die-cast aluminum housing.

SHIELDING

Clear prismatic acrylic is standard. Optional white acrylic and clear prismatic polycarbonate.

ELECTRICAL

Energy saving and electronic class P, HPF ballasts comply with Federal Energy Efficiency standards.

FINISH

All exterior parts finished in architectural bronze stage polyester powder coat. Optional white finish. All reflecting surfaces are finished with baked white enamel.

CERTIFICATION

All units bear UL label. Listed for wet location. Made in U.S.A.

<u>MODEL</u>	<u>LAMP QTY</u>	<u>WATTAGE</u>	<u>TYPE</u>	<u>VOLTAGE</u>
CVPL	1	PL7	CF-Compact	120V
	2	PL9	Fluorescent	277V
		PL13		UNV
	1	35 50	HPS-High Pressure Sodium	

OPTIONS

- TP** – Tamperproof hardware
- WA**– White Opal Acrylic Lens
- LEX**-Prismatic Polycarbonate Lens
- WH**- White Finish Housing

JOB NAME:

FIXTURE TYPE:

MODEL NO:

