

DIMENSIONS



Dimensions are subject to change. For critical applications, verify all dimensions with factory.



ORDERING

Ideal for parking areas, entrances, walkways, underpasses, loading docks, recreation areas, and tunnels. Heavy-duty die-cast aluminum back housing. Color matched UV stabilized polycarbonate front housing with ribbed lens area. Front Housing is hinged for easy relamping. One piece designed anodized aluminum reflector for optimum light efficiency. Silicon rubber seal prevents leakage. Lamping in compact fluorescent in 2-18 watt, 2-26 watt, 2-32 watt and 2-42 watt and 35W, 50W and 70W HPS available.

HOUSING

Heavy-duty die cast aluminum back housing.

ELECTRICAL

Compact fluorescent standard with universal voltage electronic ballast. HPS standard with 120 volt normal power factor magnetic core and coil ballast.

SHIELDING

Polycarbonate diffuser is standard.

FINISH

Powder coated architectural bronze is standard. Other finishes are available upon request.

CERTIFICATION

UL listed for wet locations.

<u>MODEL</u>	<u>LAMP QTY</u>	<u>WATTAGE</u>	<u>TYPE</u>	<u>VOLTAGE</u>
WPB	1	18	CF-	UNV
	2	26	Compact	
		32	Fluorescent	
		42		

OPTIONS:

- PC** – Photocell (Specify Voltage)
- TP** – Tamperproof hardware
- GLR** – Fusing
- CF** – Compact Fluorescent
- CC** – Custom Color
- REM** – Remote Emergency Pack



JOB NAME:
FIXTURE TYPE:
MODEL NO: