


**DIMENSIONS**



Dimensions are subject to change. For critical applications, verify all dimensions with factory.



**ORDERING**

Die cast rear aluminum housing with one piece UV stabilized polycarbonate front cover. Available in high pressure sodium 50W-100W, metal halide 50W-100W and compact fluorescent 26W-42W. Dark sky friendly lighting aims light 15° below the horizontal. Hydroformed aluminum reflector improves fixture performance. All units are provided with 1/2" threaded apertures allowing for surface conduit installation and/or optional photocell. All units fully gasketed for weather tight construction. All units may mount directly over standard 4" outlet boxes.

**HOUSING**

Rugged die cast aluminum rear housing.

**ELECTRICAL**

For metal halide lamping, ballast is high power factor, constant wattage auto transformer. Electrical components are mounted to cast aluminum housing for optimum heat dissipation. For high pressure sodium, ballast is normal power factor reactor type for 120V. High power factor, multi-tap, and most fixed voltages available. Compact fluorescent supplied with universal voltage electronic ballast.

**SHIELDING**

UV stabilized injection molded polycarbonate internally finished to match rear housing.

**FINISH**

Baked on premium architectural bronze for maximum durability.

**CERTIFICATION**

All units bear UL labels. UL listed for wet and damp locations. Made in U.S.A.

<u>MODEL</u> TCWP	<u>WATTAGE</u>	<u>TYPE</u>	<u>VOLTAGE</u>
	50	PSMH-Pulse	120
	70	Start Metal	277
	100	Halide	480
		HPS-High Pressure Sodium	MULTI
	26	CF-Compact	120
	32	Fluorescent	277
	42		UNV

**ADDITIONAL OPTIONS:**

- EM** - 90 Min. Remote Battery Back-Up (For Compact Fluorescent Only)
- PC** - Photocell
- TP** - Tamperproof hardware
- GLR** - Fusing
- QZ** - Quartz Restrike
- CC** - Custom Color

JOB NAME:
FIXTURE TYPE:
MODEL NO:

