


DIMENSIONS



Dimensions are subject to change. For critical applications, verify all dimensions with factory.



ORDERING

Available in

- 70W-150W Pulse Start Metal Halide
- 4 light 42W Compact Fluorescent
- 100W Induction

Ideal for parking areas, entrances, walkways, underpasses, loading docks, and on building exteriors. Anodized aluminum reflector offers high reflectivity and ease of maintenance. Induction System is an electrode-less technology that offers an unprecedented 80,000 hour lamp life and is virtually maintenance free. This fixture works well in extreme conditions. The induction lamp operates in very cold temperatures and delivers up to 10 times the lumen output of the more traditional lighting in these environments.

HOUSING

Heavy duty die-cast aluminum housing.

ELECTRICAL

High Power Factor, constant wattage autotransformer available in fixed voltage or multi-tap.

REFLECTOR

Two piece aluminum reflector upper section removes to create uplight

CERTIFICATION

All units bear UL label. Made in U.S.A. UL listed for wet location, covered ceiling mount only.

MODEL
GL

LAMP QTY
1

WATTAGE
70
100
150

TYPE
PSMH-
Pulse Start
Metal Halide

VOLTAGE
120
480
MULTI

2
4

42

CF-
Compact
Fluorescent

UNV

1

100

IND-
Induction

120
277

OPTIONS:

- PC** – Photocell
- TP** – Tamperproof hardware
- GLR** – Fusing
- QZ** – Quartz Restrike
- HS** – 180° Cutoff Shield
- CC** – Custom Color



JOB NAME:
FIXTURE TYPE:
MODEL NO: