


# 1. Recessed

# Ultra Shallow Center Direct

# US/CD15

## DIMENSIONS



Dimensions are subject to change. For critical applications, verify all dimensions with factory.



## ORDERING

Available in 1x4, 2x2 and 2x4 in 2 lamp T5 and T5-HO versions. Provides subtle direct with, soft, uniform indirect illumination. Ultra shallow design allows for areas with critically limited plenum space. Shielding is easily removed for relamping. Flanged fixture available for plaster ceilings. Surface mount version maximizes overhead ceiling space.

### HOUSING

Die formed 20 gauge steel housing unitized into one piece.

### ELECTRICAL

Energy saving electronic ballasts comply with Federal Energy Efficiency standards. Ballasts are <10% THD and include 5 year manufacturer's warranty. Ballasts operate on 120V-277V (UNV) unless specified otherwise.

### SHIELDING

White split perforated steel diffuser with acrylic inlay. Optional solid perforated basket

### FINISH

All metal parts pretreated with a phosphate bonding process and post-painted with electrostatically applied high temperature baked matte white enamel for superior quality and durability.

### CERTIFICATION

All units bear UL label. Made in U.S.A. ARRA and BAA compliant.

MODEL	SIZE	LAMP QTY	WATTAGE/TYPE	VOLTAGE
US/CD15 (1.5" depth)	1 – 1x4	2	28T5 54T5HO	120 277 UNV
	2 – 2x2	2	14T5 24T5HO 40BX	
	2 – 2x4	2	28T5 54T5HO	

## OPTIONS

- EM** - Emergency
- DM** - Dimming (specify)
- Prefix M (M-US/CD15)** – Flanged Unit
- Prefix S (S-US/CD15)** – Surface Mounting
- SOLID** – Solid Perforated Diffuser
- SPLIT** – Split Perforated Diffuser
- FA** – Frosted Acrylic Diffuser
- OA** – Opal Acrylic Diffuser



JOB NAME:
FIXTURE TYPE:
MODEL NO: