


1. Recessed

Recessed Wall Wash

RWW



DIMENSIONS



Dimensions are subject to change. For critical applications, verify all dimensions with factory.



ORDERING

Linear Wall Wash unit utilizes a unique "kicker" reflector to provide maximum wall illumination with minimum glare. Eliminates hot spots and shadows on vertical surfaces. High performance specular reflector provides 95% reflectance and is designed to shield the lamp from room side and 9 degree cut-off from wall side. Fixture housing flanges rolled to eliminate sharp edges. Engineered ballast compartment for maximum heat dissipation. Available with open bottom or with semi-specular cross baffle for a softer wash.

HOUSING

Die formed Code gauge steel unitized into one piece. The reflector is anodized aluminum.

ELECTRICAL

Energy saving electronic ballasts comply with Federal Energy Efficiency standards. Ballasts are <10% THD and include 5 year manufacturer's warranty. Ballasts operate on 120V-277V (UNV) unless specified otherwise.


FINISH

All parts are painted with high gloss baked white enamel with minimum 89% reflectance applied over iron phosphate pretreatment for maximum adhesion and rust resistance.

CERTIFICATION

All units bear UL label. Made in U.S.A. Suitable for damp location. ARRA and BAA compliant.

<u>MODEL</u>	<u>LAMP QTY/TYPE</u>	<u>VOLTAGE</u>	<u>OPTIONS</u>
RWW-24"	1-40BX	120	EM – Emergency
	1-17T8	277	DM – Dimming
	1-14T5	UNV	SCB – Semi Specular Cross Baffle
	1-24T5HO		DM – Electronic Dimming
RWW-48"	2-40BX		
	1-32T8		
	1-28T5		
	1-54T5HO		



JOB NAME:

FIXTURE TYPE:

MODEL NO:

