

DIMENSIONS



Dimensions are subject to change. For critical applications, verify all dimensions with factory.



ORDERING

Compact fluorescent alternative to HID hi-bay applications. Instant-on, eliminating the need for quartz restrike, added capabilities for multi-switching, dimming, and emergency modes. Utilizes 4 or 6 lamps in 26W, 32W, or 42W highly efficient compact fluorescent lamps. Ideal for warehouses, cafeterias, gymnasiums or any application where dimming or multi-level switching is preferred. Engineered ballast compartment for maximum heat dissipation.

HOUSING

Round die cast housing

BALLAST/MOUNTING

Energy Efficient Electronic Ballasts are standard. Optional dimming ballasts. Standard with 3/4" hub for pendant mounting. Standard with hook, optional cord and plug.

REFLECTOR/REFRACTOR

Acrylic refractor is standard.

CERTIFICATION

All units bear UL label. Made in U.S.A. Suitable for damp location. ARRA compliant.

<u>MODEL</u>	<u>LAMP QTY</u>	<u>WATTAGE</u>	<u>VOLTAGE</u>
CFHB	4	26CF	120
	6	32CF	277
	4	42CF	UNV
	6		

OPTIONS:

- EM** - Emergency
- DM** - Dimming (Specify type)
- WG** - Wire Guard
- CP6** - 6' Cord & Plug



JOB NAME:
FIXTURE TYPE:
MODEL NO: