


DIMENSIONS



Dimensions are subject to change. For critical applications, verify all dimensions with factory.



ORDERING

Compact fluorescent alternative to HID hi-bay applications. Instant-on, eliminating the need for quartz restrike, added capabilities for multi-switching, dimming, and emergency modes. Utilizes 8 lamps in 26W, 32W & 42W. Ideal for warehouses, cafeterias, gymnasiums or any application where dimming or multi-level switching is preferred. Engineered ballast compartment for maximum heat dissipation. Wide variety of lenses and wire guards to meet virtually any lighting requirement.

<u>MODEL</u>	<u>LAMP QTY</u>	<u>WATTAGE</u>	<u>VOLTAGE</u>
CFHB	8	42CF	120 277 UNV

HOUSING

Round die cast housing

BALLAST/MOUNTING

Energy Efficient Electronic Ballasts are standard. Contains (4) 2 lamp ballasts. Optional dimming ballasts. Standard with 3/4" hub for pendant mounting. Standard with hook, optional cord and plug.

REFLECTOR/REFRACTOR

Acrylic refractor is standard.

CERTIFICATION

All units bear UL label. Made in U.S.A. Suitable for damp location. ARRA compliant.

OPTIONS:

- EM** - Emergency
- WG** - Wire Guard
- CP6** - 6' Cord & Plug



JOB NAME:
FIXTURE TYPE:
MODEL NO: