




**DIMENSIONS**



Dimensions are subject to change. For critical applications, verify all dimensions with factory.



**ORDERING**

Available in nominal 2', 3' and 4' lengths in 1 or 2-lamp configurations, T5 or T5-HO. Fully assembled housing for individual or continuous row mounting. Predrilled mounting holes for easy installation. Can be fed through end or back of unit. Suitable for low density ceiling applications. Symmetric, asymmetric, and light shield and swivel adjustable reflectors available. Available with specular aluminum reflector (87% reflectance) high efficiency white reflector (92% reflectance) or high efficiency specular aluminum reflector (95% reflectance).

**HOUSING**

Die formed heavy gauge steel housing with ample knockouts for ease of installation.

**ELECTRICAL**

Energy saving electronic ballasts comply with Federal Energy Efficiency standards. Ballasts are <10% THD and include 5 year manufacturer's warranty. Ballasts operate on 120V-277V (UNV) unless specified otherwise.

**FINISH**

All parts pre-painted with high gloss baked white enamel with minimum 89% reflectance applied over iron phosphate pretreatment for maximum adhesion and rust resistance.

**CERTIFICATION**

All units bear UL label. Made in U.S.A. Suitable for damp location. ARRA and BAA compliant.

<u>MODEL</u>	<u>LAMP QTY</u>	<u>WATTAGE/TYPE</u>	<u>VOLTAGE</u>
ST2	1	14T5 (22-7/16")	120
	2	24T5HO (22-7/16")	277
		21T5 (34-9/32")	UNV
		39T5HO (34-9/32")	
		28T5 (46-1/16")	
		54T5HO (46-1/16")	

**OPTIONS:**

- EM** - Emergency
- DM** - Dimming
- SA95** - High Efficiency Specular Reflector
- SA87** - Specular Reflector
- WH92** - High Efficiency White Reflector
- SR** - Symmetric Reflector
- AR** - Asymmetric Reflector
- LS** - Wall Wash Light Shield
- WG** - Wire Guard
- CK** - Chain Kit



JOB NAME:
FIXTURE TYPE:
MODEL NO: