



**DIMENSIONS**



Dimensions are subject to change. For critical applications, verify all dimensions with factory.



**ORDERING**

Available in 4 sizes to suit most commercial, classroom, and residential applications. Narrow 6-1/2" wide unit is available in 2', 4', and 8' lengths. 1 and 2 lamp, T8 and T5. 11-1/4" wide unit is available in 2', 4' and 8' lengths, in a two-lamp configuration, T8 and T5. 15-1/4" wide unit is available in 2', 4', and 8' lengths, 2, 3, and 4 lamp configurations, T8 and T5. Integral embossed white end plates with flush knockouts make fixtures suitable for individual or continuous row mounting. Diffuser hinges from either side for ease of service. Flat bottom and linear ribbed sides provide excellent light control. For surface or pendant mounting. Available with energy efficient reflectors in High Efficiency Aluminum (95% reflectance), Specular Aluminum (87% reflective) and High Efficiency White (92% reflectance.)

**HOUSING**

Die formed heavy guage steel with leveling embossments, which allow direct mounting on most combustibile low density ceilings. NYC approved 20 gauge steel available.

**ELECTRICAL**

Energy saving electronic ballasts comply with Federal Energy Efficiency standards. Ballasts are <10% THD and include 5 year manufacturer's warranty. Ballasts operate on 120V-277V (UNV) unless specified otherwise.

**SHIELDING**

100% clear acrylic prismatic diffuser is standard.

**FINISH**

All parts finished with high gloss baked white enamel with 89% reflectance applied over iron phosphate pretreatment for maximum adhesion and rust resistance.

**CERTIFICATION**

All units bear UL label. Suitable For damp location. Made in U.S.A. ARRA and BAA compliant.

<u>MODEL</u>	<u>LAMP QTY</u>	<u>WATTAGE/TYPE</u>	<u>VOLTAGE</u>	
<b>67</b>	2' unit	2 17T8	120	
		3 14T5	277	
		4 24T5HO	UNV	
	4' unit	2 32T8		
		3 28T5		
		4 54T5HO		
	8' unit	2 32T8-8TD		
		3 28T5-8TD		
		4 54T5HO-8TD		
	<b>67N- (Narrow Width)</b>			
	2' unit	1 17T8		
		2 14T5		
2 24T5HO				
4' unit	1 32T8			
	2 28T5			
	2 54T5HO			
8' unit	1 32T8-8TD			
	2 28T5-8TD 54T5HO-8TD			

**OPTIONS:**  
**EM** -Emergency  
**DM** - Dimming  
 (Specify Type)  
**SA95-** High Efficiency Aluminum Reflector  
**SA87-** Specular Aluminum Reflector  
**WH92** -High Efficiency White Reflector  
**20G-** 20 Gauge Steel  
**FRC-** Full Reflector Cover (3 lamp versions required for pendant mounting.)



JOB NAME:
FIXTURE TYPE:
MODEL NO: