




DIMENSIONS



Dimensions are subject to change. For critical applications, verify all dimensions with factory.



ORDERING

Ribbed opal acrylic diffuser for soft, even illumination. Slim 4-5/8" width housing ideal for narrow corridors. This versatile fixture can be surface, pendant, or wall mounted. For individual or continuous row mounting with optional joiner bands. End plates are die formed with full perimeter flange for lens retention and light tight fit. Available with integral motion sensor for stairwell applications.

HOUSING

Die formed heavy gauge steel housing.

ELECTRICAL

Energy saving electronic ballasts comply with Federal Energy Efficiency standards. Ballasts are <10% THD and include 5 year manufacturer's warranty. Ballasts operate on 120V-277V (UNV) unless specified otherwise.

SHIELDING

100% virgin acrylic opal ribbed is standard. Smooth white acrylic is also available.

FINISH

All parts finished with high gloss baked white enamel with minimum 89% reflectance applied over iron phosphate pretreatment for maximum adhesion and rust resistance.

CERTIFICATION

All units bear UL label. Made in U.S.A. Suitable for damp location. ARRA and BAA compliant.

<u>MODEL</u>	<u>LAMP QTY</u>	<u>WATTAGE/TYPE</u>	<u>VOLTAGE</u>
159	1	17T8	120
		25T8	277
		32T8	UNV
		14T5	
		21T5	
		28T5	
		54T5HO	
		32T8-8TD	
		28T5-8TD	
		54T8-8TD	

OPTIONS:

- EM** – Emergency
- DM** – Dimming
- SWA** – Smooth White Acrylic Lens
- JB** – Joiner Band



JOB NAME:
FIXTURE TYPE:
MODEL NO: