

DIMENSIONS



Dimensions are subject to change. For critical applications, verify all dimensions with factory.



ORDERING

Available in 1x2, 1x4, 2x2, 2x4 sizes, in 2, 4, and 6 lamp configurations, T5, T8 and BIAx. One piece seamless cast re-entrant acrylic diffuser provides uniform light diffusion with minimal brightness and contrast. Diffuser hinges from either side with no visible hardware. Matte black finish of the housing further disguises the shallow depth of the fixture. All white housing is available as an option. Designed for individual, surface, or pendant mount.

HOUSING

Die formed heavy gauge steel housing welded into one piece for maximum strength.

ELECTRICAL

Energy saving electronic ballasts comply with Federal Energy Efficiency standards. Ballasts are <10% THD and include 5 year manufacturer's warranty. Ballasts operate on 120V-277V (UNV) unless specified otherwise.

FINISH

Premium coat baked white enamel paint used on all reflecting interior surfaces. Matte black baked enamel on all exterior surfaces.

CERTIFICATION

All units bear UL label. Made in U.S.A. Suitable for damp location. ARRA and BAA compliant.

<u>MODEL</u>	<u>LAMP QTY/TYPE</u>	<u>VOLTAGE</u>	<u>OPTIONS</u>
CPX-1 1x2 unit	2-17T8	120	EM - Emergency DM - Dimming WH - All White Housing
	1-31U	277	
	2-BIAx40	UNV	
	2-14T5		
CPX-1 1x4 unit	2-32T8		
	4-32T8		
	2-28T5		
	4-28T5		
CPX-2 2x2 unit	4-17T8		
	6-17T8		
	2-32T8U6		
	2-BIAx40		
	4-24T5		
CPX-2 2x4 unit	6-24T5		
	2-32T8		
	4-32T8		
	6-32T8		
	2-28T5		
	4-28T5		
	6-28T5		



JOB NAME:
FIXTURE TYPE:
MODEL NO: