

DIMENSIONS



Dimensions are subject to change. For critical applications, verify all dimensions with factory.



ORDERING

Available in 18", 2', 3', and 4' lengths in 1 and 2 lamp configurations, T8 and T5 in compact fluorescent lamping. Versatile fixture can be mounted individually, or in continuous rows. Wall or ceiling, vertical or horizontal mounting. Available with optional open ends. ADA compliant with 4" projection and 8" width. Optional switch for wall mount or auxiliary applications.

HOUSING

Heavy gauge die formed steel back plate. Front bars are heavy gauge aluminum

ELECTRICAL

Energy saving electronic ballasts comply with Federal Energy Efficiency standards. Ballasts are <10% THD and include 5 year manufacturer's warranty. Ballasts operate on 120V-277V (UNV) unless specified otherwise.

FINISH

Back plate finished in premium grade white enamel. Decorative bars finished in natural aluminum.

SHIELDING

Smooth opal acrylic diffuser is standard.

CERTIFICATION

All units bear UL label. Made in U.S.A. Suitable for damp location. ARRA and BAA compliant.

<u>MODEL</u> WLV	<u>LAMP QTY - WATTAGE/TYPE</u>	<u>VOLTAGE</u> 120 277 UNV
(18" Length)	1 - PL13	
(2' Length)	1 - F17T8	
	2 - F17T8	
	1 - F14T5	
	2 - F14T5	
(3' Length)	1 - F25T8	
	2 - F25T8	
	1 - F21T5	
	2 - F21T5	
(4' Length)	1 - F32T8	
	2 - F32T8	
	1 - F28T5	
	2 - F28T5	

OPTIONS:

- DM** – Dimming
- EM** – Emergency
- SW** – Turn Switch
- OE** – Open ends



JOB NAME:
FIXTURE TYPE:
MODEL NO: