




**DIMENSIONS**



Dimensions are subject to change. For critical applications, verify all dimensions with factory.



**ORDERING**

Slim, easy to install unit utilizing highly efficient L.E.D. units provided with ultra bright diodes. Reliable and cost efficient unit is ideal for any commercial or industrial application where high performance and contemporary design is required. Available in single or double face for ceiling or wall mount. Includes canopy. Directional chevrons must be advised. Total energy consumption of 3 watts. Test switch and indicator light located at end of unit. To meet various local codes, units are also available with optional green letters, 8" letters, or flashers, when required. Automatic low-voltage disconnect, brownout protection Emergency models provided with solid state charging system and maintenance free lead calcium batteries.

**HOUSING**

Anodized extruded aluminum housing. Clear acrylic face. Optional white or mirrored face.

**ELECTRICAL**

LED have a 25 year life expectancy and utilize only 3 watts

**CERTIFICATION**

All units bear UL label and Made in the U.S.A. label. Meets or exceed NEC, OSHA, NFPA, and most state and local codes.

**MODEL**

**EDG6-**  
6" Letters  
(Standard)

**EDG8-**  
8" Letters  
(NYC)

**TYPE**

**AC -**  
AC Only

**PP -**  
Battery  
Backup

**FACE**

**1 -**  
Single Face

**2 -**  
Double Face

**OPTIONS:**

**WF** – White Face

**MF** – Mirror Face

Directional Chevrons must be specified

**G** – Green Letters



JOB NAME:
FIXTURE TYPE:
MODEL NO: