


7. Task & Wall Brackets

Corridor Fixture

MPOC



DIMENSIONS



Dimensions are subject to change. For critical applications, verify all dimensions with factory.



Available in 2', 3', & 4' lengths in 1 or 2 light versions in T8 and T5 applications. Ribbed opal acrylic diffuser for soft, even illumination. Slim housing ideal for Stairwells and corridors. This versatile fixture can be surface, or wall mounted. End plates are die formed with full perimeter flange for lens retention and light tight fit.

HOUSING

Die formed heavy gauge aluminum housing.

ELECTRICAL

Energy saving electronic ballasts comply with Federal Energy Efficiency standards. Ballasts are <10% THD and include 5 year manufacturer's warranty. Ballasts operate on 120V-277V (UNV) unless specified otherwise. Sensor is manufactured by the Watt Stopper Corp.

SHIELDING

100% virgin acrylic opal ribbed is standard.

FINISH

All parts standard with high gloss baked white enamel finish with minimum 89% reflectance applied over iron phosphate pretreatment for maximum adhesion and rust resistance. Optional chrome or brass finishes

CERTIFICATION

All units bear UL label. Made in U.S.A. Suitable for damp location. ARRA and BAA compliant.

ORDERING

MODEL MPOC	LAMP	WATTAGE	VOLTAGE
2' unit	1	17T8	120V
	2		277V UNV
3' unit	1	25T8	
	2		
4' unit	1	32T8	
	2	14T5	
		21T5	
		28T5	
		PL13	
		PL15	
	1	BIAX40	

OPTIONS:

- EM** - Emergency
- DM** - Dimming
- SWA** - Smooth White Acrylic
- CH** - Chrome Finish
- BR** - Brass Finish
- OC** - Occupancy Sensor

JOB NAME:
FIXTURE TYPE:
MODEL NO:

