

DIMENSIONS



Dimensions are subject to change. For critical applications, verify all dimensions with factory.



ORDERING

Compact unit that accommodates 4 remote adjustable fixtures. Ideal for public, commercial, and industrial facilities with varied unit load requirements. Metal incandescent heads are standard. Optional plastic or weatherproof heads. Remote battery powered. Available in 6 volt, 12 volt and 24 volt Battery units have low voltage disconnects that prevents possible over-discharge of battery. Automatic brownout protection is standard. Test switch and indicator pilot light are standard. Optional voltmeter. Overall dimension are 8" x 8 "x 8" with standard heads. Mounts to 4" octagon box

<u>MODEL</u>	<u>BATTERY</u>	<u>HEADS</u>	<u>VOLTAGE</u>	<u>OPTIONS</u>
QUAD4	6V 12V 24V	PL - Plastic WP - Weatherproof	120 277 UNV	VM - Voltmeter

HOUSING

18 gauge die formed steel.

BATTERY

6, 12 or 24 volt, maintenance free, sealed lead calcium for 120V/277V system.

FINISH

Powder coat in Architectural white.

LAMPS

Glass sealed PAR36 5.4 watt high intensity tungsten lamps are standard.

CERTIFICATION

All units bear UL label and Made in the U.S.A. labels. Meets or exceed NEC, OSHA, NFPA, and most state and local codes. New York City and Chicago approved units available.



JOB NAME:
FIXTURE TYPE:
MODEL NO: