

Vapor Tight LED Low Bay

VLEDLB2-N

vapor tight led

Standard with stainless steel latches. For pendant mounting. Stainless steel mounting brackets reduce installation time and eliminate the need for mounting holes in fixture body.

Stainless steel V hooks simplify pendant mounting with chain or cable. For individual or continuous row with flexible conduit.

Housing

Heavy-duty unsaturated fiberglass reinforced polyester housing with poured in place gasketing. Flame class 5VA.

Electrical

<10% THD and includes 5 year manufacturer's warranty. Operate on 120V-277V (UNV) unless specified otherwise.

Shielding

Glass clear diffuser molded of UV stabilized, impact-resistant acrylic.

Certification

All units bear UL label. Made in U.S.A. Suitable for damp location. ARRA and BAA compliant. IP67 Certified. National Sanitation Foundation (NSF) approved components. NEMA 4X rated. Factory hose-down tested at 1500 PSI, 1.4 gallons/minute@12-24". To 190°F operating temperature. 1 year RLE warranty. 5 year or 50,000 hour manufacturer's warranty on LED's and drivers.

PROJECT	
FIXTURE	
FIXTURE 2	
APPROVED BY	DATE
NOTES	



Model	LED Channels	Voltage	Lumens
VLEDLB2-N	110 Watts Flatboard Array	UNV	15,000
VLEDLB2-HO	175 Watt High Output	UNV	20,000

Width: 14.61"



Width: 14.61" • 371mm Length: 51.91" • 1319mm Depth: 5.95" • 151mm

Options

- SSV** Stainless Steel V Hooks
 - SSMB** Stainless Steel Mounting Brackets
 - TP** Tamperproof Hardware
 - HB6OY** 5' Cable Hanging Kit
- Other lengths available.

*Dimensions are subject to change.
For critical applications, please verify all dimensions with RLE.



Stainless Steel Latches and Brackets

