

## Circular High Bay LED

CHBLED

RLE's Heavy Duty LED High Bay features a unique design with a quick disconnect cable that can quickly separate the driver from the LED module for easy maintenance. It's uniquely designed prismatic lens provides ideal lighting coverage and minimum glare. This unit has a built in heat sink and comes with a hook made of die cast aluminum for a strong and easy installation. Heavy-duty one complete piece die cast provides maximum heat dissipation.

Cooling fans are added to increase ambient temperature to 50°C standard.

### Housing

Die-formed heavy gauge aluminum unitized into one piece.

### Electrical

Driver suitable for 120v-277v operation. Philips LED system.

### Shielding

High impact polycarbonate frosted lens.

### Finish




UV stabilized powder coated finish. White is standard. Also available in bronze.

### Certification

All units bear UL label. Suitable for wet location. IP66 Rated. ARRA and BAA compliant. Standard 5-year warranty. 4000K and 5000K are DLC Premium. DLC listed with OEM Partner.

### Options

- OCC** Occupancy Sensor
- PC** Photo Control
- PM** Pendant Mount
- BR** Bronze Finish



PROJECT	
FIXTURE	
FIXTURE	
APPROVED BY	DATE
NOTES	



### LUMENS / WATTS

TYPE	WATTS	LUMENS
250W Replacement	150W	19,113
400W Replacement	191W	24,616
1000W Replacement	212W	27,679

\*Dimensions are subject to change.  
For critical applications, verify all dimensions with RLE.

Suspended Linear

heavy-duty